



Successful Launch & Commission of TripleSat Constellation

- Start of Commercial Operational Services

Dr. Wei Sun

International Marketing Director
Twenty First Century Aerospace Technology (21AT Asia)

JACIE Workshop 2016

The Company



- EO satellite operator based in Beijing, 400+ employees
- Since 2005, the company has been providing EO data and value added service in China
- EO satellite resources:
 - ✓ Beijing-1, 4m PAN/32m MS, 2005~2012
 - ✓ 2.5m PAN/10m MS payload on Practice-9 Satellite
 - ✓ TripeSat Constellation, 1m PAN/4m MS, has been launched on 10 July 2015
- Beijing -1 International data distribution through DMC and disaster response through International Charter
- 21AT Asia in Singapore will provide TripleSat
 Constellation imagery to worldwide customers



Imagery Data Storage



21AT Satellite Resources: Beijing-1 Small Satellite


Orbit	SSO 686km
GSD	4m PAN, 32m MS
Swath Width	24km/600km
MS bands	G/R/NIR
Off- pointing	±30°
Revisit	1 day for 32m MS; 5 day for 4m PAN

Launched in 27 Oct. 2005 Operated for 7 yrs, exceed 5yrs design lifetime



DMC+4 /Beijing-1


Geospatial Data Base and its Applications




Agriculture Statistic Survey


Beijing Major Crops Monitoring (Wheat and Corn)

- ☐ Implement regional wheat and corn monitoring 3 times per year
- □ Accurate extraction of field area
 - Assist compensation distribution based on area
- ☐ Statistic accuracy > 95%






Information Extraction from Satellite Imagery



Information Interpretation Process





Open Golf Course





Building





Open Stadium





Cemetery





Airport





Terraced Fields





Dry land





Broad-leaved Forest





Open Pit





River





Power station






Highway





Change Detection of Interested Features



changeinformation
to the spatial
database

Regular remote sensing data acquisition and processing **Change-information extraction**

administrative data

Illegal

Legal

Compare with government

On-site verification with mobile device


Update the



Dismantlement enforcement support

Change Monitoring of Targeted Areas






2004-8

2006-8

2007-10

2008-8






Olympic flame

Urban Change
Monitoring— to
Support the
Application
Beijing Olympic
Game 2008


Services Overview of Intelligent City Management System

More than 100 Services for 10 government departments that can be classified into 6 categories. The following is the six major government departments served:



Illegal Dumping Rubbish Surveillance

Using remote sensing technology to solve "Rubbish Surround City" problem



Illegal Dumping Rubbish Surveillance

Before After






Environment Impacts from Surrounding Provinces

- the only way to collect such information

Air pollution sources identified from satellite imagery



Air Pollution Sources Tracking

Factory pollution source demolished but appearing again nearby





2012 2014

21

Illegal Land Usages

To assist land use and mining law enforcement, frequent monitoring

- Illegal land occupation
- Damage agriculture field and surface mining resources
- Illegal sand mining

Earlier discovery, reporting and law enforcement



Agriculture land



New Golf Field



Sand Mining

Summary and Benefits

Based on Guaranteed High Resolution Satellite Imagery, 21AT Asia provides

- □ Updated, objective and independent land cover survey cost effective
 - Planning of further city development and quality of life improvement in the city
 - Evaluation of quality of life in the city
 - The bases for Change Surveillance
- □ Change Surveillance of Interested Features and Targeted Areas
 - Keep city in order running smooth and efficient
 - For law enforcement
- □ City Management Operation and Reporting Software
 - All geospatial data integration
 - Comprehensive analysis
 - Statics and various government reports
 - Government operation software

Conclusion

- ☐ The traditional ground survey and monitoring require a lot of manpower and resources, are incomplete and costly process, so that out of date
- □ In contrast, Observing from Sky provides
 - Complete picture of the city efficiently that makes the regular status update possible
 - Independent and objective data out of influence from human interest
- ☐ In addition, satellite observation provides monitoring of neighboring provinces for environment protection.


An Innovative approach for land cover survey and monitoring



Enable Intelligent City Management

TripleSat Constellation

Designed to be Compatible with IKONOS Technical Specifications



Sat. Num.	3	
Orbit	SSO, 650km LTAN:10:30am	
GSD	PAN: <1m, MS: <4m	
Swath Width	24km	
MS bands	B/G/R/NIR	
Off-pointing	±45°	
Revisit	1 day	
Manufacturer	SSTL in UK	

First purposely built <1m 3 identical satellite constellation with daily revisit capability 2

Integrated Satellites In the Manufacture - SSTL






State-Of-Art Low Cost Small Satellites

Integration with PSLV-XL Launcher







Last Glance of TripleSat in Satish Dhawan Space Centre in India


Successful Launch on 10 July

- Three <1m Satellites were launched by PSLV-XL on 10 July
- TripleSat-1, TripleSat-2 & TripleSat-3 are injected to 650km sun synchronized orbit
- Three ground stations from three different locations used for initial commissioning
 - Svalbard of Norway
 - Borden of UK
 - Guildford of UK
- Telemetry from all three satellites were received on their first pass over the dedicated ground station



Phasing for the Constellation

- One week after the launch, on board propulsion systems was fired to move the satellites to their designated positions in the constellation
- Now, they are in the designated positions, 33 minutes/120° apart
- The propulsion system will continuously maintain the satellite positions



Unique daily targeting capability made possible by three satellite constellation 29

Daily Imaging Anywhere on the Earth

- □ TripleSat Constellation launched by a single launcher
- Phasing three satellites 33 minutes after each other to form the ideal constellation
- □ Able to target anywhere on the Earth once per day using off-pointing capability (45° Max.)

	Off-pointing / revisit period			
Latitude	5°	15°	25 °	35°
0°	8 days	3 days	2 days	Daily
±10°	8 days	3 days	2 days	Daily
±20°	8 days	3 days	2 days	Daily
±30°	7 days	3 days	2 days	Daily
±40°	7 days	2 days	2 days	Daily
±50°	6 days	2 days	Daily	Daily
±60°	4 days	2 days	Daily	Daily
±70°	3 days	Daily	Daily	Daily
±80°	2 days	Daily	Daily	Daily

With frequent revisit capability, offering "dependable data" services

TripleSat Constellation – The United States Coverage

With three satellites in constellation, the whole United States can be covered within 52 days theoretically within off oppoingting < 30°





Denver, Sports Authority Field at Mile High, 2015-11-14 Denver, USA by TripleSat Constellation 14 Nov 2015 Scale 15000 Includes material © 21AT 2016, all rights reserved

Arizona, Stanfield, 2016-04-03



Washington, The White House, 2015-10-12



Washington, Washington Monument, 2015-10-12, TripleSat



Washington, Memorial Amphitheater, 2015-10-12



Beijing, China, 7th of September

C.7.2 Absolute Radiometric Calibration Accuracy

Requirements: The nominal absolute radiometric calibration accuracy for all products, shall be <7% following in-orbit vicarious calibration

	FM1	FM2	FM3
Blue	3.26%	3.27%	3.27%
Green	3.09%	3.10%	3.10%
Red	3.18%	3.14%	3.16%
NIR	3.30%	3.11%	3.25%
PAN	3.44%	3.29%	3.29%

C.7.3 Relative band-to-band stability

Requirements: The nominal relative band to band stability within any image shall be better than 4%

The red band was used as a reference band as it is least affected by atmospheric influences (0%)

	FM1	FM2	FM3
Blue	3.82%	1.51%	3.1%
Green	1.32%	0.57%	0.95%
Red	0%	0%	0%
NIR	1.67%	1.43%	0.34%
PAN	1.39%	0.62%	1.05%

C.7.4 Signal-to-Noise Ratio (SNR)

Requirements:

The SNR for Very High Resolution Imager (VHRI) products, before ground processing, shall be at least 100:1 (1-sigma) for all channels

The SNR was calculated for 6 CDS using 2 TDI stages on the Multispectral bands and 16 TDI stages on the PAN band.

Band	SNR
Blue	220:1
Green	230:1
Red	200:1
NIR	145:1
PAN	170:1

C.7.5 MTF

Requirements:

For the VHRI the in-orbit MTF on axis, disregarding atmospheric effects, shall be:

VHRI-PAN: >10% (at PAN Nyquist frequency)

VHRI-MS/Blue: >20% (at colour Nyquist frequency)

VHRI-MS/Green: >20% (at colour Nyquist frequency)

VHRI-MS/Red: >20% (at colour Nyquist frequency)

VHRI-MS/NIR: >20% (at colour Nyquist frequency)

	Average MTF@Nyquist		
	FM1	FM2	FM3
Blue	35.0%	37.9%	31.5%
Green	37.5%	38.0%	38.5%
Red	37.5%	39.0%	35.5%
NIR	32.9%	34.5%	24.3%
PAN	20.6%	19.1%	17.3%

C.9.2 Geo-location (2 Star Trackers)

Requirement:

In a condition where the Sun, Earth or Moon are not in the blinding zones of either star tracker, the geo-location accuracy at nadir after ground processing, shall be <50m (1 σ) (without GCPs)

During commissioning suitable image data was captured from all three satellites and compared with a reference data set

NAIP dataset, http://viewer.nationalmap.gov/viewer/). For height control a digital elevation model was used (CGIAR SRTM v4, http://srtm.csi.cgiar.org/)

The data captured during this test had AOCS data from two star trackers

	FM1	FM2	FM3
RMS x [m]	7	6	6
RMS y [m]	17	13	16

Started Commercial Operation Services in April 2016

- After the completion of
 - Radiometric and Geometric Calibration
 - Performance verification tests
- The initial service will start in the middle of November 2015


Specifications	Contract Value	In Orbit Result
SNR	>100:1	145 - 230
MTF	Pan >10% MS > 20%	17.3% - 20.6% 24.3% - 39%
Swath width	23.4km	24km
Geo-location	<50m	<20m

Benefits to Worldwide Customers

- Dependable data source for operational monitoring
 - Able to target anywhere on the Earth once per day with high resolution image
- ☐ The best combination of spatial resolution and time resolution
 - <1m GSD with 24km swath
- □ Compatible technical specifications with those of IKONOS
 - Well understood applications
- Identical payloads plus cross calibration over three satellites
 - Convenient for quicker applications
- ☐ In addition to along track Stereo imaging by single satellite, cross track Stereo imaging by adjacent satellites
 - Made possible by three satellites in a constellation
- Cloud free image selection for efficient download
 - Enabled by large on-board memory
- "Operational monitoring of the Changes intelligent management"
 - Creating new business opportunity for our customers
- □ Comprehensive application expertise
 - Provide in depth application supports

Future Plan

☐ Open for Participation in TripleSat Constellation/Beijing-2



□ One of my responsibilities is to look at Beijing - 3 mission after the international sales is under way

46



Thank You!

Tel: +86-10-82927822

Fax: +86-10-82930690

Email: weisun@21at.sg

Web: www.21at.com.cn

